

Product data sheet Characteristics

PDL100MPIR

Motion Sensor Module PDL - Passive Infrared - Indoor - LED indicator - 250 V



Main Range of product PDL Sensors Product or component Sensor type Colour tint White Black 750 W incandescent Load type 100 W fluorescent 400 W halogen 100 W motor Quantity per set Set of 10

Carton

Complementary

o o p . o o		
Material	PC (polycarbonate)	
Surface finish	Glossy Matt	
[In] rated current	3 A	
Rated voltage	230250 V AC 50 Hz	
Network number of phases	1 phase	
Mounting location	Front of modular console	
Installation direction	Horizontal Vertical	
Width	23 mm	
Height	23 mm	

Type of packing

Environment

2.11 Chillion		
IP degree of protection	IP55	
Ambient air temperature for operation	-10 50 °C	

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inhered as a substitute for and is not to be used for determining suitability of these products for specific user applications. This the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.