## Product data sheet Characteristics

# PDL56E2SGY

Enclosure - Shallow, 2-Gang, 2x25mm Conduit Entry, Grey



#### Main

Range	56 Series	
Product or component type	Enclosure	
· · · · · · · · · · · · · · · · · · ·		

## Complementary

Ambient air temperature for operation -4055 °C  IP degree of protection IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 width 10.200 cm  Package 1 Length 19.800 cm	Range	56 Series	
Mounting mode         Surface mounted           Fixing center         84 x 184 mm           Number of gangs         2 x 1 gang           Material         PVC (polyvinyl chloride)           Surface finish         Gloss           Colour tint         Grey           Length         198 mm           Width         102 mm           Depth         38 mm           Quantity per set         Set of 8           Type of packing         Carton    Environment  Ambient air temperature for operation	Product or component type	Enclosure	
Mounting mode         Surface mounted           Fixing center         84 x 184 mm           Number of gangs         2 x 1 gang           Material         PVC (polyvinyl chloride)           Surface finish         Gloss           Colour tint         Grey           Length         198 mm           Width         102 mm           Depth         38 mm           Quantity per set         Set of 8           Type of packing         Carton    Environment  Ambient air temperature for operation	Complementary		
Fixing center         84 x 184 mm           Number of gangs         2 x 1 gang           Material         PVC (polyvinyl chloride)           Surface finish         Gloss           Colour tint         Grey           Length         198 mm           Width         102 mm           Depth         38 mm           Quantity per set         Set of 8           Type of packing         Carton    Environment  Ambient air temperature for operation  4055 °C  IP degree of protection  IP66  Packing Units  Package 1 Weight  300.000 g  Package 1 Height  4.000 cm  Package 1 width  10.200 cm  Package 1 Length  19.800 cm  Offer Sustainability  Offer Sustainability	<u> </u>	Surface mounted	
Material PVC (polyvinyl chloride)  Surface finish Gloss  Colour tint Grey  Length 198 mm  Width 102 mm  Depth 38 mm  Quantity per set Set of 8  Type of packing Carton  Environment  Ambient air temperature for operation P66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 Length 19.800 cm  Offer Sustainability	Fixing center	84 x 184 mm	
Surface finish Gloss Colour tint Grey Length 198 mm Width 102 mm Depth 38 mm Quantity per set Set of 8 Type of packing Carton  Environment Ambient air temperature for operation -4055 °C IP degree of protection IP66  Packing Units Package 1 Weight 300.000 g Package 1 width 10.200 cm Package 1 Length 19.800 cm  Offer Sustainability	Number of gangs	2 x 1 gang	
Colour tint Grey Length 198 mm Width 102 mm Depth 38 mm Quantity per set Set of 8 Type of packing Carton  Environment Ambient air temperature for operation -4055 °C IP degree of protection IP66  Packing Units Package 1 Weight 300.000 g Package 1 Height 4.000 cm Package 1 Length 19.800 cm  Offer Sustainability	Material	PVC (polyvinyl chloride)	
Length 198 mm  Width 102 mm  Depth 38 mm  Quantity per set Set of 8  Type of packing Carton  Environment  Ambient air temperature for operation -4055 °C  IP degree of protection IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 width 10.200 cm  Package 1 Length 19.800 cm  Offer Sustainability	Surface finish	Gloss	
Width 102 mm  Depth 38 mm  Quantity per set Set of 8  Type of packing Carton  Environment  Ambient air temperature for operation -4055 °C  IP degree of protection IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 width 10.200 cm  Package 1 Length 19.800 cm  Offer Sustainability	Colour tint	Grey	
Depth 38 mm  Quantity per set Set of 8  Type of packing Carton  Environment  Ambient air temperature for operation -4055 °C  IP degree of protection IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 Length 19.800 cm  Offer Sustainability	Length	198 mm	
Quantity per set Set of 8  Type of packing Carton  Environment  Ambient air temperature for operation -4055 °C  IP degree of protection IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 width 10.200 cm  Package 1 Length 19.800 cm  Offer Sustainability	Width	102 mm	
Type of packing  Carton  Environment  Ambient air temperature for operation -4055 °C  IP degree of protection  IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 width 10.200 cm  Package 1 Length 19.800 cm  Offer Sustainability	Depth	38 mm	
Environment  Ambient air temperature for operation -4055 °C  IP degree of protection IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 width 10.200 cm  Package 1 Length 19.800 cm  Offer Sustainability	Quantity per set	Set of 8	
Ambient air temperature for operation -4055 °C  IP degree of protection IP66  Packing Units  Package 1 Weight 300.000 g  Package 1 Height 4.000 cm  Package 1 width 10.200 cm  Package 1 Length 19.800 cm			
Packing Units Package 1 Weight 300.000 g Package 1 Height 4.000 cm Package 1 width 10.200 cm Package 1 Length 19.800 cm	Type of packing	Carton	
Packing Units Package 1 Weight 300.000 g Package 1 Height 4.000 cm Package 1 width 10.200 cm Package 1 Length 19.800 cm  Offer Sustainability	Environment		
Package 1 Weight         300.000 g           Package 1 Height         4.000 cm           Package 1 width         10.200 cm           Package 1 Length         19.800 cm   Offer Sustainability	Environment Ambient air temperature for operation	-4055 °C	
Package 1 Height         4.000 cm           Package 1 width         10.200 cm           Package 1 Length         19.800 cm   Offer Sustainability	Environment Ambient air temperature for operation	-4055 °C	
Package 1 width 10.200 cm Package 1 Length 19.800 cm  Offer Sustainability	Environment Ambient air temperature for operation IP degree of protection	-4055 °C	
Package 1 Length 19.800 cm  Offer Sustainability	Environment Ambient air temperature for operation IP degree of protection Packing Units	-4055 °C IP66	
Offer Sustainability	Environment  Ambient air temperature for operation  IP degree of protection  Packing Units  Package 1 Weight	-4055 °C IP66	
·	Environment Ambient air temperature for operation IP degree of protection  Packing Units Package 1 Weight Package 1 Height	-4055 °C IP66 300.000 g 4.000 cm	
·	Environment  Ambient air temperature for operation  IP degree of protection  Packing Units  Package 1 Weight  Package 1 Height  Package 1 width	-4055 °C IP66 300.000 g 4.000 cm 10.200 cm	
EU RoHS Directive Under investigation	Environment Ambient air temperature for operation IP degree of protection  Packing Units Package 1 Weight Package 1 Height Package 1 width	-4055 °C IP66 300.000 g 4.000 cm 10.200 cm	
	Environment Ambient air temperature for operation IP degree of protection  Packing Units Package 1 Weight Package 1 Height Package 1 width Package 1 Length  Offer Sustainability	-4055 °C IP66 300.000 g 4.000 cm 10.200 cm	
	Environment Ambient air temperature for operation IP degree of protection  Packing Units Package 1 Weight Package 1 Height Package 1 width Package 1 Length  Offer Sustainability	-4055 °C IP66 300.000 g 4.000 cm 10.200 cm 19.800 cm	

### Environment

Ambient air temperature for operation	-4055 °C	
IP degree of protection	IP66	2

## **Packing Units**

Package 1 Weight	300.000 g	
Package 1 Height	4.000 cm	
Package 1 width	10.200 cm	
Package 1 Length	19.800 cm	

#### Offer Sustainability

EU RoHS Directive	Under investigation