Product data sheet Characteristics

PDL56E1/25/25GY

Enclosure, 1-Gang, 2x25mm 1x32mm Conduit Entry, Grey



Main

Range	56 Series	
Product or component type	Enclosure	

Complementary

Range	56 Series	
Product or component type	Enclosure	
Complementary		
Mounting mode	Surface mounted	
Fixing center	84 x 84 mm	
Number of gangs	1 gang	
Material	PVC (polyvinyl chloride)	
Surface finish	Gloss	
Colour tint	Grey	
Length	102 mm	
Width	102 mm	
Depth	63 mm	
Depth Quantity per set	63 mm Set of 12	
Quantity per set Type of packing Environment	Set of 12 Carton	
Quantity per set Type of packing Environment Ambient air temperature for operation	Set of 12 Carton -4055 °C	
Quantity per set Type of packing Environment	Set of 12 Carton	
Quantity per set Type of packing Environment Ambient air temperature for operation IP degree of protection	Set of 12 Carton -4055 °C	
Quantity per set Type of packing Environment Ambient air temperature for operation IP degree of protection Packing Units	Set of 12 Carton -4055 °C IP66	
Quantity per set Type of packing Environment Ambient air temperature for operation IP degree of protection	Set of 12 Carton -4055 °C	
Quantity per set Type of packing Environment Ambient air temperature for operation IP degree of protection Packing Units Package 1 Weight	Set of 12 Carton -4055 °C IP66	
Quantity per set Type of packing Environment Ambient air temperature for operation IP degree of protection Packing Units Package 1 Weight Package 1 Height	Set of 12 Carton -4055 °C IP66 235.000 g 6.300 cm	
Quantity per set Type of packing Environment Ambient air temperature for operation IP degree of protection Packing Units Package 1 Weight Package 1 Height Package 1 width	Set of 12 Carton -4055 °C IP66 235.000 g 6.300 cm 10.000 cm	
Quantity per set Type of packing Environment Ambient air temperature for operation IP degree of protection Packing Units Package 1 Weight Package 1 Height Package 1 width	Set of 12 Carton -4055 °C IP66 235.000 g 6.300 cm 10.000 cm	

Environment

Ambient air temperature for operation	-4055 °C	
IP degree of protection	IP66	2

Packing Units

Package 1 Weight	235.000 g	
Package 1 Height	6.300 cm	
Package 1 width	10.000 cm	
Package 1 Length	10.000 cm	

Offer Sustainability

EU RoHS Directive	Under investigation