

WALL MOUNTING STRAIGHT BOX SOCKETS **SERIES 690**

MAIN TECHNICAL FEATURES:

- 20° Inclined industrial sockets according to the Standard EN 60309.
- Wall mounting straight box, ready for conduit Ø 20 or 25 mm.
- In currents of 16 and 32 A.
- Resistance to chemical or atmospheric agents.
- Stainless steel springs for lid closing.
- Dimensions 96x96x70 (WxHxD) mm.

CE

IP44

Wall mounting straight box sockets - EN 60309 - In 16A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC694001D		2P	20-25 V~	without reference	12
EC694011D		3P	20-25 V~	without reference	12
EC691001D		2P+⊕	100-130 V~	4	12
EC691011D		3P+⊕	100-130 V~	4	12
EC690501D		2P+⊕	200-250 V~	6	12
EC692501D		3P+⊕	200-250 V~	9	12
EC690521D		3P+⊕	380-415 V~	6	12
EC690541D		3P+N+⊕	346-415 V~	6	12

Wall mounting straight box sockets - EN 60309 - In 32A - IP44

ITEM	COLOUR	POLES	NOMINAL VOLTAGE	REFERENCE h	PACKAGING PIECES
EC691021D		2P+⊕	100-130 V~	4	12
EC691031D		3P+⊕	100-130 V~	4	12
EC692521D		2P+⊕	200-250 V~	6	12
EC692531D		3P+⊕	200-250 V~	9	12
EC690561D		3P+⊕	380-415 V~	6	12
EC690581D		3P+N+⊕	346-415 V~	6	12



EC691001D



EC690501D



EC690521D