Product data sheet Characteristics

PDL44BK

Ceiling Rose; 250V, 5A, 4-Terminal, Plastic, Black





Main

Range of product	PDL Lighting and Accessories	:
Product or component type	Lamp holder	
Colour tint	Black	
Quantity per set	Set of 20	
Type of packing	Carton	

Complementary

Auantity per set Set of 20 Type of packing Carton Complementary Material Polycarbonate Surface finish Glossy In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Vetwork number of phases 1 phase Fixing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Package 1 Weight 40.000 mm Package 1 width 70.000 mm Differ Sustainability			
Range of product PDL Lighting and Accessories Product or component type Lamp holder Dolour tint Black Quantity per set Set of 20 Expre of packing Carton Complementary Material Polycarbonate Surface finish Glossy In] rated current 5 A Uelly rated operational voltage 250 V 50 Hz Veltwork number of phases 1 phase Existing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Existing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Height 40.000 mm Package 1 Length 70.000 mm Package 1 Length 70.000 mm Offer Sustainabliety Sustainable offer status Green Premium product			
Range of product PDL Lighting and Accessories Product or component type Lamp holder Dolour tint Black Quantity per set Set of 20 Expre of packing Carton Complementary Material Polycarbonate Surface finish Glossy In] rated current 5 A Uelly rated operational voltage 250 V 50 Hz Veltwork number of phases 1 phase Existing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Existing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Height 40.000 mm Package 1 Length 70.000 mm Package 1 Length 70.000 mm Offer Sustainabliety Sustainable offer status Green Premium product	Main		
Product or component type Lamp holder Colour tint Black Quantity per set Set of 20 Type of packing Carton Complementary Material Polycarbonate Surface finish Glossy In] rated current 5 A Ue] rated operational voltage Eixing mode By screws Device mounting Surface Ciampter 7 1 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals Package 1 Height 40.000 mm Package 1 Height Package 1 Length Tomo Offer Sustainability Sustainable offer status Green Premium product		PDL Lighting and Accessories	
Colour tint Black Quantity per set Set of 20 Type of packing Carton Complementary Material Polycarbonate Surface finish Glossy In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Network number of phases 1 phase Fixing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Package 1 Weight 40.000 mm Package 1 Height 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	· ·		
Auantity per set Set of 20 Type of packing Carton Complementary Material Polycarbonate Surface finish Glossy In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Network number of phases 1 phase Poixing mode By screws Device mounting Surface Diameter 71 mm 1eight 37.3 mm Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Package 1 Weight 40.000 mm Package 1 Height 70.000 mm Package 1 Length 70.000 mm Differ Sustainability Sustainable offer status Green Premium product	Colour tint		
Complementary Material Polycarbonate Surface finish Glossy In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Network number of phases 1 phase Packing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight 40.000 mm Package 1 Length 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product			
Material Polycarbonate Burface finish Glossy In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Network number of phases 1 phase Exing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Exing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Package 1 Weight 0.043 kg Package 1 Weight 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Type of packing	Carton	
Material Polycarbonate Burface finish Glossy In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Network number of phases 1 phase Exing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Exing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Package 1 Weight 0.043 kg Package 1 Weight 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product			
Material Polycarbonate Burface finish Glossy In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Network number of phases 1 phase Exing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Exing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Package 1 Weight 0.043 kg Package 1 Weight 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Complementary		
In] rated current 5 A Ue] rated operational voltage 250 V 50 Hz Network number of phases 1 phase Fixing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Green Premium product	Material	Polycarbonate	
Uej rated operational voltage 250 V 50 Hz Network number of phases 1 phase Eixing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Eixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight 40.000 mm Package 1 width 70.000 mm Package 1 Length Offer Sustainability Green Premium product	Surface finish	Glossy	
Network number of phases 1 phase Fixing mode By screws Device mounting Surface Diameter 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals Packing Units Package 1 Weight Package 1 Height 40.000 mm Package 1 Length 70.000 mm Package 1 Length Offer Sustainability Green Premium product	[In] rated current	5 A	
Existing mode By screws Device mounting Surface 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals Packing Units Package 1 Weight Package 1 Height Package 1 width Package 1 Length Package 1 Length Offer Sustainability Offer Sustainable offer status Green Premium product	[Ue] rated operational voltage	250 V 50 Hz	
Device mounting Surface 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight 0.043 kg Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Network number of phases	1 phase	
Diameter 71 mm Height 37.3 mm Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight 0.043 kg Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Fixing mode	By screws	
Height 37.3 mm 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight 0.043 kg Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Device mounting	Surface	
Fixing center 52.1 mm Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight 0.043 kg Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Diameter	71 mm	
Connections - terminals 3 x 1.5 mm² screw terminal Packing Units Package 1 Weight Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length Offer Sustainability Sustainable offer status Green Premium product	Height	37.3 mm	
Package 1 Weight 0.043 kg Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Fixing center	52.1 mm	
Package 1 Weight 0.043 kg Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Connections - terminals	3 x 1.5 mm² screw terminal	
Package 1 Weight 0.043 kg Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product			
Package 1 Height 40.000 mm Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Packing Units		
Package 1 width 70.000 mm Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Package 1 Weight	0.043 kg	
Package 1 Length 70.000 mm Offer Sustainability Sustainable offer status Green Premium product	Package 1 Height	40.000 mm	
Offer Sustainability Sustainable offer status Green Premium product	Package 1 width	70.000 mm	
Sustainable offer status Green Premium product	Package 1 Length	70.000 mm	
Sustainable offer status Green Premium product	Offer Sustainability		
·	Sustainable offer status	Green Premium product	
		·	

Packing Units

Package 1 Weight	0.043 kg	To an
Package 1 Height	40.000 mm	. <u>.</u>
Package 1 width	70.000 mm	
Package 1 Length	70.000 mm	etro. Ti

Offer Sustainability

Sustainable offer status	Green Premium product

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	