

Product data sheet

Characteristics

PDL347VH-VW

Switch Iconic - Assembled - Marked COOKER
 - Vertical - 1-gang - Double-pole - 250 V - 45 A
 - Vivid White



Main

Range of product	PDL Iconic
Product or component type	Switch
Device presentation	Complete switch
Provided equipment	Grid plate Skin Screws Switch
Device application	Cooking appliances
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 5
Sale per indivisible quantity	1
Load type	Inductive

Complementary





Device mounting	Flush
Switch function	1-pole 1-way
Number of gangs	1 gang horizontal/vertical 84 mm
Number of rocker	1
Actuator	Rocker
Fixing mode	By screws
Surface finish	Matt
Surface treatment	Untreated
Rated current	45 A at 250 V AC 50 Hz
Electrical durability	5000 cycles conforming to AS/NZS 60669
Connections - terminals	6 screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	6 mm ² for stranded cable(s)
Wire stripping length	10 mm
Material	PC (polycarbonate): skin ABS (acrylonitrile butadiene-styrene): skin PC (polycarbonate): grid plate PP (polypropylene): flaps PC (polycarbonate): housing
Height	120 mm
Width	78 mm
Depth	39 mm
Net weight	0.124 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company. This information is not intended to be used as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for storage	0...60 °C
Dielectric strength	5000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Product certifications	RCM

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile