Product data sheet Characteristics

PDL576

Range Socket; 32A, 230V/400VAC - 250V/500V, 4-Pin, White



Main

Range of product	500 Series	
Product or component type	Socket	
Colour tint	White	
Quantity per set	Set of 10	
Type of packing	Carton	

Complementary

Complementary		
Control type	Rocker	#
Material	PC (polycarbonate)	
Installation direction	Horizontal	i d
Surface finish	Gloss	Salite Salite
Width	170 mm	
Height	48 mm	.i.
[le] rated operational current	10 A	E g
[Ue] rated operational voltage	220/240 V 50 Hz	
Network number of phases	1 phase	9
Number of gangs	2 gangs	
Connections - terminals	3 x 2.5 mm² terminals	+
Number of poles	3	
Device mounting	Surface	<u>.</u>
Fixing center	150 mm	Series Control of the
		<u>×</u>

Environment

Ambient air te	mperature for	operation	-1040	°C
----------------	---------------	-----------	-------	----

Packing Units

Package 1 Weight	220 g
------------------	-------

Offer Sustainability

EU RoHS Directive	Under investigation
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)