

# SMART SENSE 360° PIR SENSORS

## Flush Mount



Detection	Range	Time On Adjustable	Dusk Control	Manual Override	Max. Switching	Colour	Order Code
360° Downward	6m (dia)	5 sec - 15 min	Yes	Yes	2000W (Resistive) 110W (LED)	White	LHT0142

- Low profile, flush mounted sensor for soffit or internal mounting
- Capable of switching loads on different phase or voltage supply

## General Information

Cut Out for Recessing	Mounting	Safety	IP Rating	Warranty
75mm Ø	Flush	Class II	IP44	3 years

## Surface or Flush Mount



Detection	Range	High Occupancy Zone	Time On Adjustable	Dusk Control	Manual Override	Max. Switching	Colour	Order Code
360° Downward	22m (dia) Adjustable	6m	10 sec - 40 min	Yes	Yes	2000W (Resistive) 200W (LED)	White	LHT0179

- Triple PIR for extra wide 22 metre detection
- All in one surface or recess mount
- Occupancy detection high/low sensing zones

## General Information

Cut Out for Recessing	Mounting	Safety	IP Rating	Warranty
82mm - 88mm Ø	Surface or flush	Class II	IP44	3 years

## Smart Sense 360° Accessories

Description	Order Code
Replacement Mounting Accessory Pack for LHT0179	LHT0417